Nail-on, Flanged Vapor Box for Devices

Prevents Air Infiltration in New Construction



EASY NAIL-ON INSTALLATION

Back

view

Position Vapor Box; attach to stud with captive nails. Pull cable through installed cable connector.

Catalog	UPC/DEI/NAED	Description	Cubic	Unit/Std
Number	Mfg. #018997	Vapor Box	Inches	Pkg
FN101FL	. 09814	Non-metallic gasketed box for devices	22.8	25/carton

Includes non-metallic box with installed NM cable connector and gaskets, two (captive) nails for box installation and (1) plug for unused knockouts.

Arlington's new non-conductive Vapor Box **nails** to a stud in new construction.

Easy to install, *this box* has gaskets that form a protective barrier that **prevents air infiltration** *inside* – to meet International

Energy Conservation Codes (IECC) and other codes where required.



For added convenience, the nails ship captive and the installed NM cable connectors and flange have the gasket material attached – there's no assembly required!

Plus, the built-in gasketed flange has ultra-thin alignment tabs so there's NO DRYWALL BULGE.

- 22.8 cubic inch non-metallic box for single 1/2" or 5/8" drywall
- UL Listed, UV rated

• 2-Hour Fire Rating





1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com