



H.264 IP Bullet Camera Varifocal

6522- 2 megapixel H.264 IP Bullet Camera

Channel Vision's 6522 IP Bullet Camera offers superior image quality with a 2 megapixel CMOS sensor and has the ability to capture images up to UXVGA (1600 x 1200 pixels). With H.264 compression, less bandwidth and storage space are used, while delivering full resolution at max frame rate.



Features

- High resolution with 2 megapixels for superior image quality
- H.264 compression allows less bandwidth and storage space to be used while delivering full resolution at max frame rate
- Varifocal lens with built-in 35 IR LED for a viewing distance of 60 feet in total darkness
- Monitoring can be done anywhere an internet connection is available, even from a 3G smartphone

Specifications*

Hardware:

- CPU:** ARM 9, 32 bit RISC
- DDR2:** 256MB
- Image Sensor:** 1/3" CMOS (2 Megapixels)
- Sensitivity:** 0 lux (IR on)
- Lens Type:** Vari-focal 3.6 to 16mm Lens
- LED:** Built-in 35 IR LED
- Alarm I/O:** 1 in/ 1 relay out
- Video Out:** x1
- Audio In:** x1
- Audio Out:** x1
- Power Consumption:** DC 12V 500mA (with IR)
- Operating Temperature:** 0 to +45° C

System:

- Video Resolution:** 1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144
- Video Adjust:** Brightness, Contrast, Sharpness, BLC, Night Mode
- Triple Streaming:** Yes
- Image Snapshot:** Yes
- Full Screen Monitoring:** Yes
- Privacy Mask:** Yes
- Compression Format:** H.264/ JPEG/ MPEG4 (3GPP only)
- Video Bitrates Adjust:** CBR, VBR
- Motion Detection:** Yes, with selectable area
- Triggered Action:** Mail, FTP, Save to SD card, Relay
- Pre/Post Alarm:** yes, configurable

- Security:** Password protection
- Firmware Upgrade:** HTTP mode, can be upgraded remotely
- Simultaneous Connection:** Up to 10
- Audio:** Yes, 2-way

*Specifications subject to change



Channel Vision Central
Structured Wiring



Channel Vision 6522
IR & Audio Equipment



ARIA™
Multi-Focus Audio



Channel Vision Technology
Modulators, Cameras, Intercoms