

**K**SERIES | **AUDIOPHILESPEAKERS**



**FACTOR**  
ELECTRONICS

[www.factorelectronics.com](http://www.factorelectronics.com)



FACTOR  
K-6IM  
Audiophile In-Wall Speaker

## EASY INSTALLATION!

All K Series speakers include a pre-construction bracket in the box



FACTOR  
ELECTRONICS  
K-SERIES K-6

Audiophile K-6  
6.5" Coaxial  
125 Watts Max

[www.factorelectronics.com](http://www.factorelectronics.com)

## SILKY SMOOTH

Add one inch silk dome aim-able tweeters with neodymium high power magnets for crystal clear high frequencies



## SCIENCE MEETS ART!

K Series crossovers feature air core inductors, ultra low tolerance capacitors, auto-resetting poly-switch tweeter protection, glass fiber circuit boards, gold plated wire terminals and a whole lotta love! That's right, did we mention that we love high-end audio! The Factor team has over 30 years of combined speaker building experience and the latest computer modeling software!



ELECTRONICS

K-SERIES K-8

Audiophile K-8  
8" Coaxial  
150 Watts Max

[www.factorelectronics.com](http://www.factorelectronics.com)



## STRONG & LIGHT!

All K Series speakers feature woven Kevlar woofer cones which produce deep clean bass and mid bass frequencies



- >> 125 watts peak power handling
- >> 6.5" woven Kevlar cone
- >> 20 oz magnet structure
- >> 1" silk dome neodymium aim-able tweeter
- >> 40Hz-22kHz frequency response
- >> 92dB 1w 1m sensitivity
- >> 9 7/8" (250.82mm) Overall diameter
- >> 8.18" (208mm) Cutout Dimensions Speaker
- >> 8.26" (210mm) Cutout Dimensions RI Bracket
- >> Includes pre-construction bracket
- >> 10 year warranty

**K-6**



- >> 125 watts peak power handling
- >> 6.5" Dual voice coil woven Kevlar cone
- >> 20 oz magnet structure
- >> 1" Dual silk dome neodymium aim-able tweeters
- >> 40Hz-22kHz frequency response
- >> 92dB 1w 1m sensitivity
- >> 9 7/8" (250.82mm) Overall diameter
- >> 8.18" (208mm) Cutout Dimensions Speaker
- >> 8.26" (210mm) Cutout Dimensions RI Bracket
- >> Includes pre-construction bracket
- >> 10 year warranty

**K-6ST**



**FACTOR** ELECTRONICS | **KSERIES** | **AUDIOPHILESPEAKERS**  
SPECIFICATIONS:



- >> 150 watts peak power handling
- >> 8" woven Kevlar cone
- >> 30 oz magnet structure
- >> 1" silk dome neodymium aim-able tweeter
- >> 40Hz-22kHz frequency response
- >> 92dB 1w 1m sensitivity
- >> 11.5" (292.10mm) Overall diameter
- >> 9.8" (249mm) Cutout Dimensions Speaker
- >> 9.88" (251mm) Cutout Dimensions RI Bracket
- >> Includes pre-construction bracket
- >> 10 year warranty

**K-8**



- >> 125 watts peak power handling
- >> 6.5" woven Kevlar cone
- >> 20 oz magnet structure
- >> 1" silk dome neodymium aim-able tweeter
- >> 40Hz-22kHz frequency response
- >> 92dB 1w 1m sensitivity
- >> Overall dimensions
- >> 8.25"W x 11.5"H (209.55mm x 292.1)
- >> Cutout Dimensions Speaker
- >> 6.92"W x 10.19"H (176mm x 259mm)
- >> Cutout Dimensions RI Bracket
- >> 7.04"W x 10.27"H (179mm x 261mm)
- >> Includes pre-construction bracket 10 year warranty

**K-61W**



