



PRODUCT DATA SHEET

1530 Shields Drive
 Waukegan, IL 60185
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

PART NUMBER: 992479-xx-08

DESCRIPTION: RG-6/U COAXIAL CABLE WITH 60% AL BRAID, FLOODED AND SWEPT TO 3.0 GHZ

APPLICATION: Direct Burial

Construction Parameters:


		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	18 AWG (1/.0403) Copper Clad Steel		0.040
Dielectric:	Foam Polyethylene color natural	0.070	0.180
Shielding:	Aluminum Polyester Fusible Foil Tape plus 60% Aluminum Braid		0.212
Flooding:	Water Block Compound		-
Jacket:	Polyethylene	0.031	0.274

Electrical Properties:

	<u>VALUE*</u>
Impedance (ohms):	75
Capacitance (pF/ft):	17
Velocity of Propagation (%):	81
Attenuation** (db/100 ft):	
10 MHz	0.8
50 MHz	1.3
100 MHz	1.65
200 MHz	3.1
400 MHz	4.12
700 MHz	6.28
1000 MHz	7.4
1200 MHz	6.60
1500 MHz	9.30
2000 MHz	9.76
2200 MHz	9.79
2500 MHz	10.13
3000 MHz	14.61

Cable Cross-section:

(NOT TO SCALE)



Miscellaneous Information:

Jacket Color: Black

Jacket Print: RG6 DIRECT BURIAL SWEPT TO 3.0 GHZ

Approximate Weight (lb/1000 ft): 23

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE

Company Name: _____

Customer Approval: _____

Date: _____

Issued: 03/10/05

* = Nominal value
 By: PEP