

# Closed Circuit Coaxial Cables


## \*\* CL2 NON-PLENUM

### RG 59/U Types 75 Ohm Copper Braid




Catalog Number	RG Type	Cond. Size	Diel. O.D.	Shield	Nom. O.D.	Nom. Imp.	Vel. Prop	Nom. Cap/Ft.	MHz	Atten. db
1525	59/U	22 Solid BC	Foam Poly. .140	B.C. 95% Braid	.242	80	78%	16.3	54-60	2.4
									82-88	3.1
									174-180	4.0
									210-216	4.3
1510/95	59/U	20 Solid BC	Foam Poly. .140	B.C. 95% Braid	.242	80	78%	16.3	54-60	2.4
									82-88	3.1
									174-180	4.0
									210-216	4.3

### RG 59/U Types 75 Ohm Copper Braid with 18/2



Catalog Number	RG Type	Cond. Size	Diel. O.D.	Shield	Nom. O.D.	Nom. Imp.	Vel. Prop	Nom. Cap/Ft.	MHz	Atten. db
1526	59/U with 18/2	22 Solid BC	Foam Poly. .140	B.C. 95% Braid	.242 x .430	80	78%	16.3	100	3.0
									200	4.5
									400	6.6
									900	10.0

### RG 59/U Types 75 Ohm Copper Braid with 18/2



Catalog Number	RG Type	Cond. Size	Diel. O.D.	Shield	Nom. O.D.	Nom. Imp.	Vel. Prop	Nom. Cap/Ft.	MHz	Atten. db
1535	59/U with 18/2	20 Solid BC	Foam Poly. .140	B.C. 95% Braid	.242 x .430	80	78%	16.3	100	3.0
									200	4.5
									400	6.6
									900	10.0

### RG 6/U Types 75 Ohm Copper Braid



Catalog Number	RG Type	Cond. Size	Diel. O.D.	Shield	Nom. O.D.	Nom. Imp.	Vel. Prop	Nom. Cap/Ft.	MHz	Atten. db
1531	6/U	18 Solid BC	Foam Poly. .180	B.C. 95% Braid	.275	75	78%	16.5	100	2.1
									200	3.9
									400	4.6

\*\* UL or ETL Listed