

## 7987R Paired - 4-Pair UTP Cable for RGB Video

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Related Documents : No. 8 for DataTwist Cables (Modified Western Electric).pdf</b></p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Description:

NanoSkew™ 24 AWG twisted pairs solid bare copper conductors, non-plenum, polyolefin insulation, skew 2.2ns/100m nominal, rip cord, PVC jacket.

### SUITABLE APPLICATIONS:

Suitable Applications Zero Skew, Low Skew, RJ45, UTP Based Video Applications, Not for data transmission requiring TIA/EIA Category qualifications, RGB

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

#### INSULATION:

Insulation Material PO - Polyolefin

#### Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

#### OUTER SHIELD:

Outer Shield Material Unshielded

#### OUTER JACKET:

Outer Jacket Material PVC - Polyvinyl Chloride  
Outer Jacket Ripcord Yes

#### OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter .195 in.

#### MECHANICAL CHARACTERISTICS:

## 7987R Paired - 4-Pair UTP Cable for RGB Video

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	31 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.
Min. Bend Radius (Install)	0.2 in.

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005

#### FLAME TEST:

UL Flame Test	UL1666 Riser
---------------	--------------

#### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	7987P

#### ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	100 Ohms
Nominal Velocity of Propagation	70 %
Typical Delay Skew (ns/100m)	2.2 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Max. Operating Voltage - UL	300 V RMS

#### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
7987R 059U1000	4 PR #24 PP PVC	U1000	20	MAROON	
7987R 059U1640	4 PR #24 PP PVC	U1640	32.8	MAROON	

Revision Number: 2      Revision Date: 08-25-2005

---

## **7987R Paired - 4-Pair UTP Cable for RGB Video**

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.