




CABLE SPECIFICATION

Issued: May 6, 2020

Revised: ---



(Representation of a 1 fiber)

ITEM: 10-002-76Y-ABNOQF

Fiber Type	Singlemode G.657.B3	Corning Clearcurve ZBL
Maximum Attenuation @ 1310/1550nm	dB/km	≤0.40/0.30
Number of Fibers	--	2
Buffer Diameter	microns	900
Storage Temperature Range	C	-40° to +70°
Operating Temperature Range	C	-20° to +70°
Max. Tensile Load for Installation	N (lbf)	533 (120)
Max. Tensile Load, Long-Term	N (lbf)	222 (50)
Min. Bend Radius, Unloaded	--	10 X O.D.
Crush Resistance (EIA 455-41)	N/cm	100
Impact Resistance (EIA 455-25)	Impacts	25
Flexing, ±90° (EIA 455-104)	Cycles	25
Cable Outside Diameter, Nom.	mm (in.)	4.8 (0.196)
Cable Weight, Nom.	kg/km (lbs./1000)	20 (14)

DESCRIPTION: 2 bend insensitive singlemode fibers in a tight-buffered design with water swellable aramid yarns and a black riser rated PVC outer jacket in a simplex construction, OFNR C(ETL)US suitable for indoor/outdoor applications.

*ITU G.657.B3

Data listed on this document are subject to normal manufacturing tolerances. Remeewire and cable reserves the right to improve, enhance and/or modify the features and specifications of Remeewire and cable products without prior notification. Remfo is a registered trademark of Remeewire and cable Products Corp. Remeewire, Remguard, Remex and Redss are trademarks of Remeewire and cable Products Corp.

Note: While Remeewire and cable Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeewire and cable Products Corp. does not guarantee that it is error-free, nor does Remeewire and cable Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeewire and cable Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeewire and cable Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.